



TREVI SERIES - Coloured Base Porcelain (Rectified)







BIANCO 30 x 60 cm (12" x 24") Matte Finish KJ.TR.BIA.1224 **ARGENTO** 30 x 60 cm (12" x 24") Matte Finish KJ.TR.ARG.1224 **CREMA** 30 x 60 cm (12" x 24") Matte Finish KJ.TR.CRM.1224

All items shown in this document are part of Olympia's stocking program. For special orders, please contact your Olympia Tile Sales Representative.



TREVI SERIES

Tests Performed -- Results Conform

Test	Standard Used	Min. Requirements	Results
Water Absorption	ISO 10545-3	< 0.5%	Conforms
Bending / Breaking Strength	ISO 10545-4	>1300N	Conforms
Slip Resistance	DIN 51130/51097	R-9	Conforms
Visible Surface Abrasion Resistance	ISO 10545-7	PEI 4	Conforms
Chemical Resistance	ISO 10545-13	min. UB	Conforms
Frost Resistance	ISO 10545-12	Required	Conforms
Stain Resistance	ISO 10545-14	> Class 3	Conforms

Technical data is supplied by the manufacturer and is subject to change at any time. Olympia does not provide warranties as to the specifications of any product.



Examples of Recommended Applications



Packing Details

TILE SIZE	PC/BOX	SF/BOX	LB/BOX	BOX/PAL
12" x 24" Matte	8	15.50	45.12	32





Recommended FLEXTILE Installation Systems

For other suitable options & complete installation details, visit www.flextile.net

PRODUCT	WALL APPLICATION		FLOOR APPLICATION	
	Interior	Exterior	Interior	Exterior
TILE BOND COAT	• 66 FlexLite PM Mortar • 55 LHT Mortar • 56SR LHT Mortar	• 5400 Maxi-Flex • 51/44 Latex Mortar System	• 55LHT LHT Mortar • 56SR LHT Mortar	• 5400 Maxi-Flex • 51/44 Latex Mortar System
GROUT	 500 PM Unsanded 600 PM Sanded 1600UPG PM Grout 	• 600 PM Sanded • 1600UPG PM Grout	• 600 PM Sanded • 1600UPG PM Grout • FlexEpoxy 100 Epoxy Grout	• 600 PM Sanded • 1600UPG PM Grout
CAULKING	Ultra Performance (colour-matched to grout)	Ultra Performance (colour-matched to grout)	Ultra Performance (colour-matched to grout)	Ultra Performance (colour-matched to grout)

SURFACE PREPARATION (If Required)

- Floor levelling: 59 Flex Flo / 5900 Flex Flo Plus Self Levelling Underlayment
- Waterproofing: WP900 Waterproof Membrane
- Crack Isolation/Uncoupling: Flexilastic 1000 Crack Isolation Membrane / FlexMat Uncoupling Membrane

* For a complete listing of FLEXTILE products and accessories including Sound Control, In-Floor Heating, and further setting options, please visit www.flextile.net

	"MORE" Surface Care Product Guide			
Task	Product Recommendation	Dilution with Water	Frequency	
Grout Sealing	MORE™ Grout, Ceramic & Porcelain Sealer	Ready to use	Commercial: 1-3 Years Residential: 5-8 Years	
Daily Maintenance	MORE [™] Stone and Tile Cleaner	1 : 128 Ratio	Daily	
Deep Cleaning	MORE [™] Alkaline Cleaner	1:4 Ratio	As Needed	
Grout Haze- Cementitious	MORE [™] Acidic Cleaner	1 : 4 Ratio	As Needed	
Grout Haze - Epoxy / Urethane	MORE™ Coating Stripper*	Ready to use	As Needed	

* Always test in an inconspicuous area to make sure the product is achieving the desired results and is not damaging the finish of the surface.







olympiatile+stone®



olympiatile+stone